

# RAD SINGLE SPEED

**Extreme duty torque wrenches for heavy duty applications!  
Also available with built-in transducers - visit the RAD TV Series!**


More than 25 years of experience in gearbox engineering and design has brought about our latest generation in planetary gearboxes – RAD Single Speed. Designed for extreme duty use in a variety of industries worldwide, RAD Single Speed torque wrenches offer:

- The ultimate in power-to-weight ratio
- Wide torque range to suit multiple applications
- Unmatched reliability delivered by one of the most advanced engineered gear boxes on the market
- Controlled torque - accuracy of +/- 4% and repeatability of +/- 2%



## FRL Unit:

- Low weight tool holder made from high-density polypropylene
- Includes pressure gauge, filter, regulator and oiler



PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (ft. lbs.)		RPM	WEIGHT (lbs.)	NOISE LEVEL	DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
			LOW	HIGH							
12316	350SL	0.75"	50	350	65	6.0	80 db	6.6"	2.4"	2.75"	8.75"
12814	7GX	0.75"	100	700	30	8.0	80 db	9.0"	2.5"	2.75"	9.0"
12818	10GX	0.75"	200	1000	20	8.0	80 db	8.15"	2.5"	2.75"	8.07"
17328	15DX	1.0"	300	1500	10	8.6	80 db	8.0"	2.7"	2.75"	8.1"
12377	25GX	1.0"	500	2500	9	13.5	85 db	9.7"	3.1"	3.3"	9.5"
22238	30DX	1.0"	900	3000	8	14.8	85 db	10"	3.2"	3.3"	9.5"
12356	*34GX	1.0"	1000	3400	12	20.0	85 db	12.5"	3.4"	3.7"	10.8"
20248	50DX	1.5"	1500	5000	6.7	23.5	85 db	11.25"	3.75"	3.75"	10.4"
15328	60DX	1.5"	2000	6000	6.6	27.6	85 db	13.7"	4.0"	4.0"	10.9"
18558	80DX	1.5"	2500	8000	4	30.5	85 db	12.15"	4.25"	4.25"	10.65"
26152	110DX	1.5"	4000	11000	3	42.0	85 db	13.9"	5.0"	5.0"	11.07"